

GLXSS SE



IP67

Tightness upgrade

MIL-STD

Army standard critical
conditional test

12xAI

Performance
signifigate upgrade

modularize

Magnetic smart
module

Foldable

Easier to carry

Explosion-proof

*Explosion-proof
certification

* Explosion-proof version of GLXSS SE needs to be used together with specified USB data cable.

GLXSS SE

Product Appearance



GLXSS SE

Specifications



VPU

Intel® Movidius™ Myriad™ 2
Intel® Movidius™ Myriad™ X

AI

Laffe™ AI Engine

Memory

LPDDR3 512MB

Operation system (Smart phones)

Compatible with Android
5.1 - 10.0

Display

FOV: 20° (diagonal)
Resolution: 640x400
Contrast: 100000:1

Interaction

Customized button
Gesture control
Voice control
Mobile client side
Blue tooth remote control

Sensors

6-axis sensor
Compass
Light sensor

Audio

Input: Digital mic Anti-noise
Output: Single speaker

Camera

Camera: 8 Megapixels/16 Megapixels
Record: 1080P HD video
Privacy: LED indicator

Interface

USB Type-C 2.0

Weight

30 grams (Smart module)
45 grams (Contains glasses frame)

Size

159mm x 180mm x 34mm
